

Illumine

Range of handrails with discreet LED INSERTS spaced to suit the needs of the client



January 2016

HANDRAIL OPTIONS:

- * 1. The original “warm to the touch” DDA compliant handrail (**Stargard**)
42 mm or 50 mm diameter handrail
4 mm - (4,000 microns) thick PVC sleeving over galvanized steel tube
- * 2. Brass (**Citadel**)
38 mm or 50 mm diameter handrail polished or clear lacquered
- * 3. Stainless steel (**Sentinel**)
42 mm, or 48 mm diameter handrail, grade 316 for exterior or grade 304 for interior applications
- * 4. Powder coated
42 mm, or 48 mm diameter handrail

Illumine LED INSERTS have the advantage of being able to be fitted around curved handrail

LIGHTING:

- * Individual LED light INSERTS securely fixed into the steel core of the handrail at between 250 mm and 1,000 mm centres
- * Light INSERTS are 316 stainless steel with the radius of the dome head at 21 mm (for 42/44 dia handrail) or 25 mm (for 48/50 dia handrail)
- * The installed lumen output of the INSERT is 119 Lm (5700 k)
- * Anticipated life of INSERT is 100,000 hours
- * Dimming and emergency options are available and motion sensors can be used to control the INSERTS

AC power requirement is 100v - 240v
Reference: BS 5266-1 emergency lighting
H1 b Code of practice

“Stargard” warm to the touch handrail with LED INSERTS



LED INSERT into “warm to the touch” handrail



LED INSERT HANDRAIL OPTIONS



“Sentinel” stainless steel with LED INSERTS



DATA SHEET

www.handrailsuk.co.uk

SG System Products Limited
22 Wharfedale Road
Ipswich
IP1 4JP

Tel: 01473 240055
Fax: 01473 461616
Email: sales@sgsystems.co.uk